## NSN 5305-01-103-6590

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-103-6590 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.115 inches and 0.135 inches **Fastener Length:** 0.420 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** 0.077 inches **First Diameter From Head:** 0.295 inches Point Style: Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Hardness Rating: 262.0 brinell standard **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582, type 303, cond a assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** 

Mil-f-14072, e-300 military specification single treatment response

**Test Data Document:** 

98230-0n535911 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:** 

Unc

## NSN 5305-01-103-6590

Externally Relieved Body Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
riig.

Mil-std (military Standard):

Mil-f-14072 spec.