

View Online at <https://aerobasegroup.com/nsn/5305-01-103-8816>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.381 inches and 0.431 inches

Fastener Length:

Between 0.579 inches and 0.609 inches

Head Style:

Oval countersunk

Head Diameter:

Between 0.2966 inches and 0.3016 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

High-torque

End Application:

Tf-33 engine; milstar system; aircraft, phantom f-4; aircraft, eagle f-15; a-10 thunderbolt; f/a-18 hornet; harrier

Thread Diameter:

0.190 inches

Grip Length:

Between 0.178 inches and 0.198 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

101.0 degrees

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488 type 2 cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.