NSN 5305-01-104-1066

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-104-1066

Thr	ead Class:
3a	
Thr	read Direction:
Rig	ht-hand
Thr	read Length:
Bet	ween 0.381 inches and 0.431 inches
Fas	stener Length:
Bet	ween 0.891 inches and 0.921 inches
Hea	ad Style:
Ova	al countersunk
Hea	ad Diameter:
Bet	ween 0.2966 inches and 0.3016 inches
Gri	p Diameter:
Bet	ween 0.1885 inches and 0.1895 inches
Inte	ernal Drive Style:
Hig	h-torque
Thr	read Diameter:
0.1	90 inches
Gri	p Length:
Bet	ween 0.490 inches and 0.510 inches
Thr	eady Qty Per Inch (tpi):
32	
Co	untersink Angle:
101	.0 degrees
Mat	terial:
Ste	el comp xm-13
Mat	terial Specification:
Am	s 5629 assn standard single material response
Sur	face Treatment:
Alu	minum and chromate
Sur	face Treatment Specification:
Mil-	c-83488 type 2 cl 3 military specification single treatment response
Thr	read Series Designator:
Unj	f
She	elf Life:
N/a	
Uni	it Of Measure:
Der	militarization:
No	
Fiig	j:
A00	03b0

NSN 5305-01-104-1066

Close Tolerance Screw - Page 2 of 2

Mil-std (military Standard):

Mil-c-83488 spec.

