## NSN 5305-01-104-3902

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-104-3902

| Thread Class:  |
|--|
|  |
| 3a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.568 inches   |
| Fastener Length:   |
| 2.750 inches   |
| Head Style:  |
| Flat chamfer   |
| Head Diameter:   |
| Between 0.921 inches and 0.938 inches                      |
| Head Height:   |
| Between 0.616 inches and 0.625 inches                      |
| Locking Feature:   |
| Patch threads or strip threads                             |
| Internal Drive Style:                                      |
| Hexagon  |
| Thread Diameter:   |
| 0.625 inches   |
| Width Across Flats:  |
| 0.375 inches   |
| Thready Qty Per Inch (tpi):                                |
| 11   |
| Min. Tensile Strength (psi):                               |
| 170000 pounds per square inch                              |
| Hardness Rating:   |
| 38.0 rockwell c and 45.0 rockwell c                        |
| Material:  |
| Steel fastener   |
| Surface Treatment:   |
| Zinc fastener  |
| Surface Treatment Specification:                           |
| Astm b633 assn standard single treatment response fastener |
| Thread Series Designator:                                  |
| Unc  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |

## NSN 5305-01-104-3902

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

