## NSN 5305-01-105-1142



Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-105-1142 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.381 inches and 0.431 inches **Fastener Length:** Between 0.579 inches and 0.609 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.338 inches and 0.381 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:** 

High-torque

**Thread Diameter:** 

0.190 inches **Grip Length:** 

Between 0.178 inches and 0.198 inches

**Features Provided:** 

Dry film lubricant

Thready Qty Per Inch (tpi):

32

**Countersink Angle:** 

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp xm-13

**Material Specification:** 

Ams 5629 assn standard single material response

**Surface Treatment:** 

Aluminum

**Surface Treatment Specification:** 

Mil-c-83488 military specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## NSN 5305-01-105-1142

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.