NSN 5305-01-105-5235

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-105-5235 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.097 inches **Fastener Length:** Between 0.787 inches and 0.797 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.422 inches and 0.438 inches **Head Height:** Between 0.055 inches and 0.060 inches **First Diameter From Head:** Between 0.237 inches and 0.247 inches **Second Diameter From Head:** Between 0.203 inches and 0.219 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.031 inches and 0.047 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.235 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 2 Material: Stainless steel **Material Specification:** Qq-s-763, class 303 federal specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unf Shelf Life:

N/a

NSN 5305-01-105-5235

Externally Relieved Body Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0