## NSN 5305-01-105-7185

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-105-7185 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.187 inches **Fastener Length:** Between 0.615 inches and 0.635 inches **Head Style:** Fillister **Head Diameter:** Between 0.208 inches and 0.224 inches **Head Height:** Between 0.086 inches and 0.094 inches **First Diameter From Head:** Between 0.085 inches and 0.105 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.398 inches and 0.418 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-105-7185

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0