NSN 5305-01-106-1122

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-106-1122

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.375 inches
Fastener Length:
Between 1.228 inches and 1.328 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.577 inches and 0.635 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Shank Unthreaded Hole Diameter:
0.076 inches first hole and 0.086 inches first hole
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.3125 inches
Grip Length:
0.938 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Distance From Head Largest Bearing Surface To Shank Hole Center:
1.194 inches first hole
Material:
Steel
Surface Treatment:
Cadmium and chromate
Thread Series Designator:
Unif
Specification Data:
80205-nas1205 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-106-1122

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0