

View Online at <https://aerobasegroup.com/nsn/5305-01-106-1122>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 1.228 inches and 1.328 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.577 inches and 0.635 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.3125 inches

Grip Length:

0.938 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.194 inches first hole

Material:

Steel

Surface Treatment:

Cadmium and chromate

Thread Series Designator:

Unjf

Specification Data:

80205-nas1205 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0