NSN 5305-01-106-2356

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-106-2356 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.616 inches and 0.666 inches **Fastener Length:** Between 2.188 inches and 2.218 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.510 inches and 0.564 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.375 inches **Grip Length:** Between 1.552 inches and 1.572 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** 101.0 degrees Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment:** Aluminum and chromate Mil-c-83488 type 2 cl 3 military specification single treatment response

Surface Treatment Specification: Thread Series Designator: Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig: A003b0

NSN 5305-01-106-2356

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-83488 spec.