## NSN 5305-01-106-3856

**Thread Class:** 

3a

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-106-3856

Thread Direction:
Right-hand
Thread Length:
1.000 inches
Fastener Length:
Between 1.460 inches and 1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.188 inches and 0.190 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
80000 pounds per square inch
Minimum Yield Strength:
40000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384
Material Specification:
66 federal standard all material responses
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-34 federal specification single treatment response

## NSN 5305-01-106-3856

Socket Head Cap Screw - Page 2 of 2



A003b0