

View Online at <https://aerobasegroup.com/nsn/5305-01-106-5172>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.260 inches and 0.290 inches

Fastener Length:

1.025 inches

Head Style:

Flat countersunk

Head Diameter:

0.270 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Single Shear Strength:

95000 pounds per square inch

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

0.750 inches

Thready Qty Per Inch (tpi):

32

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4130 or steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-6758 military specification 1st material response or mil-s-5626 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, class 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.