## NSN 5305-01-106-7523

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-106-7523 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.298 inches and 0.348 inches **Fastener Length:** Between 0.620 inches and 0.650 inches **Head Style:** Pan **Head Diameter:** Between 0.302 inches and 0.322 inches **Head Height:** Between 0.122 inches and 0.133 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 32 Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5737 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2, class 2 federal specification single treatment response **Thread Series Designator:** Unf **Specification Data:** 80205-nas7803 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-106-7523

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0