## NSN 5305-01-108-0648

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-108-0648

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.408 inches and 0.500 inches
Fastener Length:
Between 0.470 inches and 0.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
Between 0.156 inches and 0.159 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Minimum Yield Strength:
155000 pounds per square inch
Hole Configuration Style:
Round longitudinal hole
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5737 assn standard single material response
Surface Treatment:

Passivate

## NSN 5305-01-108-0648

Socket Head Cap Screw - Page 2 of 2



## Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unrf

**Specification Data:** 

80205-nas1351 professional/industrial association standard

**Specification Or Standard:** 

6 type

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0