NSN 5305-01-108-2505

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-108-2505

Thread Olever
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.528 inches and 0.620 inches
Fastener Length:
Between 0.590 inches and 0.620 inches
Head Style:
Fillister
Head Diameter:
Between 0.250 inches and 0.270 inches
Head Height:
Between 0.106 inches and 0.113 inches
Hole Diameter:
0.046 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Hole Quantity:
1
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
62000 pounds per square inch
Screw Material:
Aluminum alloy 2024
Screw Material Specification:
Qq-a-200/3 federal specification single material response or qq-a-225/6 federal specification single material response
Screw Surface Treatment:
Anodize
Screw Surface Treatment Specification:
Mil-a-8625, type 1 or 2, class 1 military specification single treatment response
Head Hole Configuration Style:
Round
Thread Series Designator:
Unc
Specification Or Standard:
1 type and 4 style
Shelf Life:
N/a

NSN 5305-01-108-2505

Machine Screw - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-a-8625 spec.