

View Online at <https://aerobasegroup.com/nsn/5305-01-108-2524>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.438 inches

Fastener Length:

Between 0.923 inches and 0.953 inches

Head Style:

Flat countersunk

Head Diameter:

0.564 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Shank Unthreaded Hole Diameter:

0.106 inches first hole and 0.111 inches first hole

Internal Drive Style:

High-torque

Thread Diameter:

0.375 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thread Qty Per Inch (tpi):

24

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.798 inches first hole and 0.838 inches first hole

Material:

Stainless steel

Material Specification:

23-112 fscm 76301 mfr ref single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-83488 type 2 class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.