## NSN 5305-01-108-3754

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-108-3754 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.246 inches and 0.312 inches **Fastener Length:** Between 0.282 inches and 0.312 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.134 inches and 0.140 inches **Head Height:** Between 0.083 inches and 0.086 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.086 inches Width Across Flats: Between 0.0781 inches and 0.0791 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-108-3754

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0