

View Online at <https://aerobasegroup.com/nsn/5305-01-109-0739>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.440 inches and 0.460 inches

**Fastener Length:**

Between 1.122 inches and 1.133 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**First Diameter From Head:**

Between 0.130 inches and 0.150 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.540 inches and 0.560 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

80000 pounds per square inch

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 302 or steel comp 303 or steel comp 304

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-f-14072, e300 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-f-14072 spec.