NSN 5305-01-109-2166

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-109-2166 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.000 inches **Fastener Length:** Between 2.210 inches and 2.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.1875 inches and 0.1900 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl 1 military specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-109-2166

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.