

View Online at <https://aerobasegroup.com/nsn/5305-01-110-7905>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.507 inches and 0.557 inches

**Fastener Length:**

Between 1.079 inches and 1.109 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.629 inches and 0.633 inches

**Head Height:**

Between 0.088 inches and 0.090 inches

**Grip Diameter:**

Between 0.3110 inches and 0.3120 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.312 inches

**Grip Length:**

Between 0.552 inches and 0.572 inches

**Thread Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Special Features:**

Furnished with one o-ring

**Material:**

Steel comp xm-13

**Surface Treatment:**

Aluminum and chromate

**Surface Treatment Specification:**

Mil-c-83488, type2, class 3 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.