
NSN 5305-01-111-1284

Socket Head Cap Screw - Page 1 of 2





Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.880 inches and 2.500 inches
Fastener Length:
Between 7.880 inches and 8.000 inches
Head Style:
Flat chamfer
Head Diameter:
Between 1.107 inches and 1.125 inches
Head Height:
Between 0.740 inches and 0.750 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.750 inches
Width Across Flats:
Between 0.625 inches and 0.631 inches
Thready Qty Per Inch (tpi):
10
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
6 type
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-111-1284

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

