

View Online at <https://aerobasegroup.com/nsn/5305-01-111-4202>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.320 inches and 0.370 inches

**Fastener Length:**

Between 0.580 inches and 0.610 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.337 inches and 0.383 inches

**Locking Feature:**

Patch threads

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.240 inches and 0.260 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.