NSN 5305-01-111-9153

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-111-9153

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.540 inches and 0.570 inches |
| Fastener Length: |
| Between 1.475 inches and 1.495 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.449 inches and 0.507 inches |
| Locking Feature: |
| Detent ball grip |
| Grip Diameter: |
| Between 0.2480 inches and 0.2492 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.835 inches and 0.855 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Material: |
| Steel comp 631 spring or steel comp 302 spring |
| Material Specification: |
| Qq-s-763 federal specification single material response locking feature |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response or fps-3007, cage84256 mfr ref single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No

NSN 5305-01-111-9153

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0