Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-112-5967

Thread Class: 3a Thread Direction: Right-hand Thread Length: Between 0.360 inches and 0.405 inches Fastener Length: Between 0.360 inches and 0.405 inches Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Height: Between 0.272 inches and 0.281 inches Head Height: Between 0.075 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.076 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.200 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Val Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification single treatment response Thread Series Designator: Unc Shell Lifte: Na No	3a Thread Direction: Right-hand Thread Length: Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches
Thread Direction: Right-hand Thread Length: Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Netween 0.272 inches and 0.281 inches First Diameter From Head: Between 0.075 inches and 0.075 inches First Diameter From Head: Between 0.201 inches and 0.075 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.202 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.121 inches Thread Specification: Questor Style: Thread Specification: Questor Style: Stater Teatment: State Comp 302 or steel comp 304 or steel comp 305 Material Specification: Quep-35 federal specification single treatme	Thread Direction: Right-hand Thread Length: Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches
Right-hand Thread Length: Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Height: Between 0.271 inches and 0.281 inches Head Height: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Specification: Qe-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment: Passivate Material specification: Qe-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Material: N/a Dirit of Measure: - Demilitarization:	Right-hand Thread Length: Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches
Thread Length: Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Height: Between 0.272 inches and 0.281 inches Head Height: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Vaty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qap-3763 federal specification all material responses Surface Treatment: Passivate Diasivate Cap-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: Na Unc	Thread Length: Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches
Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Height: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thread Vaty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification Aufrace Treatment: Passivate Surface Treatment: Passivate Surface Treatment Specification all material responses Material Specification: Qa-p-35 federal specification single treatment response Thread Series Designator: Unc Sheif Life: Na Unc Sheif Life: Na Material: Final Chessure: Final Chessure:	Between 0.110 inches and 0.185 inches Fastener Length: Between 0.360 inches and 0.405 inches
Fastener Length: Between 0.360 inches and 0.405 inches Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Nameter: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.076 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Quep-s5 federal specification single treatment responses Surface Treatment: Passivate Surface Treatment Specification: Quep-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Fastener Length: Between 0.360 inches and 0.405 inches
Between 0.360 inches and 0.405 inches Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Height: Between 0.072 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.250 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification Qq-s763 federal specification single treatment response Surface Treatment: Pasivate Surface Treatment Specification: Qq-p.35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: Na Uni Of Measure: Demilitarization: Demilitarization:	Between 0.360 inches and 0.405 inches
Head Style: Pan Head Diameter: Between 0.272 inches and 0.281 inches Head Height: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Stele comp 302 or stele comp 304 or stele comp 305 Material Specification: Quep-36 fiederal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Quep-35 fiederal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Thread Series Designator: Na Dh	
PanHead Diameter:Between 0.272 inches and 0.281 inchesHead Height:Between 0.071 inches and 0.075 inchesFirst Diameter From Head:Between 0.075 inches and 0.078 inchesDistance From Largest Bearing Surface Of Head To End Of First Diameter:Between 0.220 inches and 0.250 inchesInternal Drive Style:Cross recess type 1Thread Diameter:0.112 inchesThread Valy Per Inch (tpi):40Externally Relieved Body Diameter Quantity:1Material:Stele comp 302 or steel comp 304 or steel comp 305Material Specification all material responsesSurface Treatment:PassivateSurface Treatment Specification single treatment responseThread Series Designator:UncSheft Life:N/aUncSheft Life:N/aDirect Series Designator:Inter Series Designator:<	Head Style:
Head Diameter: Between 0.272 inches and 0.281 inches Head Height: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qu-ps-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qu-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	
Between 0.272 inches and 0.281 inches Head Height: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment: Passivate Surface Treatment: Qa-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Pan
Head Height: Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment: Qa-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Head Diameter:
Between 0.071 inches and 0.075 inches First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.272 inches and 0.281 inches
First Diameter From Head: Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Head Height:
Between 0.075 inches and 0.078 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: - Demilitarization:	Between 0.071 inches and 0.075 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	First Diameter From Head:
Between 0.220 inches and 0.250 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Between 0.075 inches and 0.078 inches
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Cross recess type 1 Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Between 0.220 inches and 0.250 inches
Thread Diameter: 0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Internal Drive Style:
0.112 inches Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: 	Cross recess type 1
Thready Qty Per Inch (tpi): 40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Thread Diameter:
40 Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	0.112 inches
Externally Relieved Body Diameter Quantity: 1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Thready Qty Per Inch (tpi):
1 Material: Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	40
Material:Steel comp 302 or steel comp 304 or steel comp 305Material Specification:Qq-s-763 federal specification all material responsesSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:	Externally Relieved Body Diameter Quantity:
Steel comp 302 or steel comp 304 or steel comp 305 Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	1
Material Specification: Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Material:
Qq-s-763 federal specification all material responses Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Steel comp 302 or steel comp 304 or steel comp 305
Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Material Specification:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Qq-s-763 federal specification all material responses
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment:
Qq-p-35 federal specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Passivate
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Surface Treatment Specification:
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	Qq-p-35 federal specification single treatment response
Unc Shelf Life: N/a Unit Of Measure: Demilitarization:	
N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
 Demilitarization:	Unit Of Measure:
	 Demilitarization:

NSN 5305-01-112-5967

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

