NSN 5305-01-112-7873

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-112-7873 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.479 inches and 0.581 inches **Fastener Length:** Between 0.656 inches and 0.687 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.442 inches and 0.507 inches **Locking Feature:** Pellet threads or strip threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4340 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1189 professional/industrial association standard Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-112-7873

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0