---

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-112-7873



comp 6150 or steel comp 4340

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.479 inches and 0.581 inches
Fastener Length:
Between 0.656 inches and 0.687 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.442 inches and 0.507 inches
Locking Feature:
Pellet threads or strip threads
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-112-7873

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

