

View Online at <https://aerobasegroup.com/nsn/5305-01-113-0548>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.295 inches and 0.325 inches

**Fastener Length:**

Between 0.668 inches and 0.708 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.292 inches and 0.332 inches

**Head Height:**

0.170 inches

**Material Accommodated Thickness:**

Between 0.106 inches and 0.116 inches

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Material:**

Steel comp 301 fastener or steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener or steel comp 305 fastener or steel comp 308 fastener or steel comp 309 fastener or steel comp 309s fastener or steel comp 310 fastener or steel comp 310s fastener or steel comp 314 fastener or steel comp 316 fastener or steel comp 316l fastener or steel comp 317 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 348 fastener or steel comp 384 fastener or steel comp 385 fastener

**Material Specification:**

Qq-a-225/9 federal specification single material response stand-off

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-5541 spec.