NSN 5305-01-113-2872



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-113-2872 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.315 inches and 0.320 inches **Fastener Length:** 0.882 inches **Head Style:** Hexagon **Head Height:** 0.290 inches Width Between Flats: 0.250 inches **Shoulder Diameter:** 0.163 inches first shoulder and 0.167 inches first shoulder **Shoulder Length:** 0.562 inches first shoulder and 0.567 inches first shoulder **Shank Unthreaded Hole Diameter:** 0.062 inches first hole and 0.064 inches first hole **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Distance From Head Largest Bearing Surface To Shank Hole Center: 0.500 inches first hole **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc

0110

Shelf Life:

N/a

NSN 5305-01-113-2872

Shoulder Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0