

View Online at <https://aerobasegroup.com/nsn/5305-01-113-9737>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.240 inches and 0.260 inches

**Fastener Length:**

Between 0.547 inches and 0.577 inches

**Head Style:**

Knurled no. 2

**Head Diameter:**

Between 0.500 inches and 0.515 inches

**Head Height:**

Between 0.240 inches and 0.260 inches

**First Diameter From Head:**

Between 0.115 inches and 0.125 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.178 inches and 0.198 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.164 inches

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Point 0.110 in. Min, 0.140 in. Maximum lg; 0.110 in. Min, 0.120 in. Maximum dia

**Material:**

Steel comp 303

**Material Specification:**

Astm a582 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0