NSN 5305-01-113-9737

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-113-9737 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.240 inches and 0.260 inches **Fastener Length:** Between 0.547 inches and 0.577 inches **Head Style:** Knurled no. 2 **Head Diameter:** Between 0.500 inches and 0.515 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.178 inches and 0.198 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Point 0.110 in. Min, 0.140 in. Maximum Ig; 0.110 in. Min, 0.120 in. Maximum dia Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-113-9737

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0