## NSN 5305-01-113-9739

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-113-9739 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.208 inches and 0.228 inches **Fastener Length:** Between 0.595 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** 0.270 inches **Head Height:** 0.097 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.367 inches and 0.417 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Color black Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 class 4 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-113-9739

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.