

View Online at <https://aerobasegroup.com/nsn/5305-01-114-0617>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 8.5 millimeters and 9.5 millimeters

**Fastener Length:**

Between 18.70 millimeters and 19.30 millimeters

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 9.0 millimeters and 10.0 millimeters

**Grip Diameter:**

Between 4.9780 millimeters and 4.9900 millimeters

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

5.0 millimeters

**Grip Length:**

Between 9.80 millimeters and 10.20 millimeters

**Thread Pitch In Millimeters:**

0.8

**Countersink Angle:**

Between 99.5 degrees and 100.5 degrees

**Surface Finish:**

0.8 micrometers threads

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Mj

**Specification Data:**

80205-na0042 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0