NSN 5305-01-114-0971

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-114-0971



or steel comp 6150 or steel comp 4340

| Thread Class: |
|---|
| |
| 3a Thread Direction |
| Thread Direction: |
| Right-hand |
| Thread Length: Between 0.378 inches and 0.428 inches |
| |
| Fastener Length: Between 2.013 inches and 2.043 inches |
| |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.464 inches and 0.507 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) Thread Diameter: |
| |
| 0.250 inches |
| Grip Length: |
| Between 1.615 inches and 1.635 inches |
| Thready Qty Per Inch (tpi): |
| |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| 36.0 rockwell c and 40.0 rockwell c |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 |
| Surface Treatment: |
| Cadmium and chromate |
| Surface Treatment Specification: |
| Qq-p-416, type 2 cl 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Specification Data: |
| 80205-nas1580 professional/industrial association standard |
| Shelf Life: |

N/a

NSN 5305-01-114-0971

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

