NSN 5305-01-114-5126

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-114-5126 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.300 inches **Fastener Length:** 2.087 inches **Head Style:** Flat chamfer **Head Diameter:** 0.375 inches **Head Height:** 0.148 inches **First Diameter From Head:** 0.230 inches **Second Diameter From Head:** 0.480 inches **Third Diameter From Head:** 0.365 inches **Fourth Diameter From Head:** Between 0.258 inches and 0.259 inches Fifth Diameter From Head: 0.140 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.707 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.737 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.987 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: **1.787** inches **Internal Drive Style:** Slot **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi):

32

Externally Relieved Body Diameter Quantity:

NSN 5305-01-114-5126

Externally Relieved Body Screw - Page 2 of 2



Material:
Steel comp 324
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0