

View Online at <https://aerobasegroup.com/nsn/5305-01-115-3413>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 1.420 inches and 1.499 inches

Fastener Length:

Between 1.484 inches and 1.531 inches

Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

Width Between Flats:

Between 0.305 inches and 0.314 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

Between 36.0 rockwell c and 40.0 rockwell c

Screw Material:

Steel comp e4340 or steel comp 8740

Screw Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams 6322 assn standard 2nd material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 type 2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1801 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.