

View Online at <https://aerobasegroup.com/nsn/5305-01-116-1192>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.376 inches and 0.438 inches

Fastener Length:

Between 0.407 inches and 0.438 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.231 inches and 0.279 inches

Head Height:

0.057 inches

Locking Feature:

Pellet or strip

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 6150 or steel comp 8735 or steel comp 8740

Locking Feature Material:

Plastic polychlorotrifluoroethylene

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-8503 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6049 military specification 5th material response

Locking Feature Material Specification:

Mil-s-18240 military specification single material response

Screw Surface Treatment:

Cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification all treatment responses

Bearing Surface Of Head Surface Finish:

32.0 microinches

Shank Surface Finish:

32.0 microinches

Thread Surface Finish:

32.0 microinches

Thread Series Designator:

Unjc

Specification Data:

80205-nas1189 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-18240 spec.