

View Online at <https://aerobasegroup.com/nsn/5305-01-116-3089>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.313 inches and 0.375 inches

**Fastener Length:**

Between 0.344 inches and 0.375 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.256 inches and 0.270 inches

**Head Height:**

Between 0.087 inches and 0.097 inches

**Locking Feature:**

Patch threads

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

36.0 rockwell c and 40.0 rockwell c

**Surface Finish:**

32.0 microinches threads

**Material:**

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 or steel comp 4340

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, ty2 cl2 federal specification single treatment response

**Thread Series Designator:**

Unjc

**Specification Data:**

80205-nas1190 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0