## NSN 5305-01-116-5436

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-116-5436 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.378 inches and 0.428 inches **Fastener Length:** Between 1.013 inches and 1.043 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.350 inches and 0.398 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.302 inches and 0.322 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 

32.0 microinches threads

Material:

Iron alloy 660

**Material Specification:** 

Ams 5732 assn standard single material response or ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

**Specification Data:** 

80205-nas1581 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5305-01-116-5436

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0