

View Online at <https://aerobasegroup.com/nsn/5305-01-116-7368>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.477 inches and 0.636 inches

**Fastener Length:**

Between 1.327 inches and 1.347 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.360 inches and 0.404 inches

**Thread Diameter:**

0.250 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Three 0.035 in. To 0.045 in. Wide splines in shank at 120 degrees

**Material:**

Steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-s-6049 military specification 1st material response or mil-s-5626 military specification 2nd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 class 2 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6049 spec.