

View Online at <https://aerobasegroup.com/nsn/5305-01-116-8095>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.625 inches

Fastener Length:

Between 2.672 inches and 2.704 inches

Head Style:

Flat countersunk

Head Diameter:

Between 1.1621 inches and 1.2815 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.625 inches

Grip Length:

Between 2.052 inches and 2.072 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

63.0 microinches grip

Material:

Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unf

Specification Data:

81205-bac30ab manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0