Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-117-5040

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.750 inches
Fastener Length:
Between 1.210 inches and 1.250 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.218 inches and 0.226 inches
Head Height:
Between 0.134 inches and 0.138 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.138 inches
Width Across Flats:
Between 0.109 inches and 0.111 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Material: Iron alloy 660
Iron alloy 660
Iron alloy 660 Material Specification:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc Specification Data:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life:
Iron alloy 660 Material Specification: Ams5731 assn standard single material response or ams5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unrc Specification Data: 80205-nas1352 professional/industrial association standard Shelf Life: N/a

No

NSN 5305-01-117-5040

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

