## NSN 5305-01-117-5923

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-117-5923

view Offilite at https://aerobasegroup.com/nsi//3303-01-11/-3923
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.270 inches and 0.381 inches
Fastener Length:
Between 1.174 inches and 1.234 inches
Head Style:
Pan
Head Diameter:
Between 0.361 inches and 0.385 inches
Head Height:
Between 0.103 inches and 0.118 inches
Shoulder Diameter:
0.186 inches first shoulder and 0.189 inches first shoulder
Shoulder Length:
0.822 inches first shoulder and 0.842 inches first shoulder
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
125000 pounds per square inch
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Shoulder Shape:
Round first shoulder
Product Name:
Navy special project
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, class 3 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1298 professional/industrial association standard

## NSN 5305-01-117-5923

Shoulder Screw - Page 2 of 2



Shelf	LIIE.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0