## NSN 5305-01-118-9604

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-118-9604 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.188 inches and 0.218 inches **Fastener Length:** Between 0.557 inches and 0.587 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Material Accommodated Thickness:** Between 0.032 inches and 0.061 inches **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 35.0 rockwell c primary washer and 43.0 rockwell c primary washer Material: Iron alloy 660 fastener **Material Specification:** Mil-s-23195 military specification single material response stand-off **Surface Treatment:** Passivate stand-off **Surface Treatment Specification:** Qq-p-35 federal specification single treatment response stand-off **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A003b0

## NSN 5305-01-118-9604

Panel Screw Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-s-23195 spec.