
NSN 5305-01-119-1052

Socket Head Cap Screw - Page 1 of 2





Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.167 inches and 0.269 inches
Fastener Length:
Between 0.344 inches and 0.375 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.491 inches and 0.507 inches
Locking Feature:
Strip threads or pellet threads or patch threads
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-119-1052

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

