NSN 5305-01-119-1978

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-119-1978 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.595 inches and 0.625 inches **Fastener Length:** Between 0.533 inches and 0.625 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.262 inches and 0.270 inches **Head Height:** Between 0.159 inches and 0.164 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.140 inches and 0.142 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell c Minimum Yield Strength: 30000 pounds per square inch Material: Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp xm-7 or steel comp 384 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type 1, class 2 federal specification single treatment response **Thread Series Designator:** Unrc **Specification Data:** 80205-nas1352 professional/industrial association standard Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-01-119-1978

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0