## NSN 5305-01-119-3149

Hexagon Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-119-3149



**Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 1.314 inches **Fastener Length:** Between 3.406 inches and 3.500 inches **Head Height:** Between 0.272 inches and 0.291 inches Width Between Flats: Between 0.612 inches and 0.625 inches **Hole Diameter:** Between 0.061 inches and 0.069 inches **Thread Diameter:** 0.438 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): 14 Min. Tensile Strength (psi): 70000 pounds per square inch Hardness Rating: 235.0 brinell standard Minimum Yield Strength: 40000 pounds per square inch **Hole Configuration Style:** Hexagon flats **Surface Finish:** 63.0 microinches threads Material: Steel comp 410 or steel comp 416f or steel comp 430 **Material Specification:** 66 federal standard all material responses **Surface Treatment:** 

**Passivate** 

**Surface Treatment Specification:** 

Qq-p-35 federal specification single treatment response

**Thread Series Designator:** 

Unc

## NSN 5305-01-119-3149

Hexagon Head Cap Screw - Page 2 of 2



Sp	ecific	ation	Or S	Stand	lard:
----	--------	-------	------	-------	-------

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0