NSN 5305-01-119-3603



Externally Relieved Body Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-119-3603 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.125 inches and 0.145 inches **Fastener Length:** 1.219 inches **Head Style:** Pan **Head Diameter:** Between 0.205 inches and 0.219 inches **Head Height:** Between 0.070 inches and 0.080 inches **First Diameter From Head:** Between 0.071 inches and 0.081 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.094 inches and 1.104 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 **Product Name:** Navy special project Material: Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 348 or steel comp 384 or steel comp comp 385 **Material Specification:** 66 federal standard all material responses **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig:

No

Demilitarization: