## NSN 5305-01-119-3628

**Thread Class:** 

Right-hand **Thread Length:**0.750 inches

**Thread Direction:** 

Fastener Length:

**Head Style:** 

Between 1.710 inches and 1.750 inches

За

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-119-3628

Flat chamfer	
Head Diameter:	
Between 0.218 inches and 0.226 inches	
Head Height:	
Between 0.134 inches and 0.138 inches	
Hole Diameter:	
Between 0.033 inches and 0.039 inches	
Internal Drive Style:	
Hexagon	
Thread Diameter:	
0.138 inches	
Width Across Flats:	
Between 0.109 inches and 0.111 inches	
Hole Quantity:	
2	
Hole Type:	
Drilled	
Thready Qty Per Inch (tpi):	
32	
Min. Tensile Strength (psi):	
180000 pounds per square inch	
Hardness Rating:	
38.0 rockwell c and 45.0 rockwell c	
Minimum Yield Strength:	
155000 pounds per square inch	
Hole Configuration Style:	
Round internal hexagon	
Material:	
Steel	
Surface Treatment:	
Cadmium and chromate	
Surface Treatment Specification:	
Qq-p-416, type 2, class 2 federal specification single treatment	response

## NSN 5305-01-119-3628

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A003b0