## NSN 5305-01-119-5035

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-119-5035 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.899 inches and 1.000 inches **Fastener Length:** Between 0.970 inches and 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.365 inches and 0.375 inches **Head Height:** Between 0.244 inches and 0.250 inches **Locking Feature:** Patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: Between 0.188 inches and 0.190 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 170000 pounds per square inch Hardness Rating: 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** 

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Thread Series Designator:** 

Unrf

**Specification Data:** 

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-119-5035

Socket Head Cap Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0