## NSN 5305-01-119-6766

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-119-6766 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.358 inches and 0.393 inches **Fastener Length:** Between 0.530 inches and 0.562 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.153 inches and 0.157 inches **Head Height:** Between 0.109 inches and 0.112 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.0781 inches and 0.0791 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 170000 pounds per square inch **Countersink Angle:** 20.0 degrees Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 type 1 or 2 or 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-119-6766

Socket Head Cap Screw - Page 2 of 2



Fiig:

A003b0